

Republic of Belarus,
517510, Gomel region,
Zhlobin, Krasny proyezd, 2g.
tel. +375 (0) 2334 4-30-30, 4-17-06
tel/fax. +375 (0) 2334 4-30-30, 4-17-06
e-mail: marketing@tanis.by
www.tanis.by



Account № 3012420061018
with CBS 402, JSC Priorbank
Zhlobin, Pervomayskaya str, 39
code 749
УНП 400518274,
ОКПО 29036220.

Close joint-stock company

«Tanis»



COMMERCIAL OFFER

We would like to offer our domestic manufacture product – **metal-polymeric rope ППШ, for vineyard and garden trellis construction.**

Metal-polymeric rope is a brass-plated metal wire covered with specific polymer that has an advanced wear resistance, weather resistance and stand the temperature from -4°C to +110°C, i.e. does not lengthen and does not sag.

Polymeric covering is neutral and stable against chemicals. The seedlings are not being scorched and damaged by wire while being repeatedly treated from plant pests and diseases.

The rope production basis is the technology developed jointly with V. Belyi Research Institute of metal-polymeric systems mechanics of the National Science Academy of the Republic of Belarus. For the first time the State Standard of the Republic of Belarus has approved the technical requirements (Specification of the Republic of Belarus 03535279.065-99) for such type of product.

Metal-polymeric rope diameter – 2.0 – 6.0 mm

Breaking strength minimum – 800 – 10 500 N.

Covering colour – black. Packing: bundles, reels. Wrapping: plastic bags, goffer boxes.

Product code	Metal-polymeric rope type	Rope diameter with covering, mm.	Diameter deviation limit, mm	Rope diameter without covering, mm	Average weight of 1 running meter, g	Rope breaking strength, not less		Sale price exclusive of VAT for 1000 running meter, EURO
						kg	N	
7312 10 490 9	ППШ-2.0	2.0	± 0.1	0.67-0.95	8,58	80	800	21,64
	ППШ-2.5	2.5	± 0.1	0.97-1.40	11,36	130	1300	26,80
	ППШ-3.0	3.0	± 0.1	1.20-2.10	17,49	220	2200	37,41
7312 10 980 9	ППШ-3.5	3.5	± 0.1	1.80-2.85	20,57	350	3500	47,46
	ППШ-4.0	4.0	± 0.13	2.0-2.90	29,72	470	4700	60,16
	ППШ-4.5	4.5	± 0.13	2.55-3.75	36,78	680	6800	72,86
	ППШ-5.0	5.0	± 0.13	2.85-3.90	50,69	825	8250	86,4
	ППШ-6.0	6.0	± 0.13	3.30-4.30	71,94	1050	10500	121,72

Brass-plated metal rope is made from steel cord (steel 70-80.) that is provided high-strength and flexibility of metal-polymeric rope. Break-offs and cut-offs by usual tools are excluded.

The Quality Certificate is attached to each delivery



Сертифицировано
Русским Регистром



Sales and marketing department: +375 (2334) 4-30-30, 4-32-32
www.tanis.by, marketing@tanis.by